


26920

Male Inverted SAE 45° - Swivel - 90° Elbow


| # Part Number | Thread | | Hose I.D. inch | A | | E | | H | J | W | B | |
|------------------|--------|---------|-------------------|------|------|------|------|------|-------|------|------|------|
| | inch | 7/16x24 | | inch | inch | mm | inch | mm | inch | inch | inch | inch |
| 26920-4-4 | 1/4 | 7/16x24 | 3/16 | 2.29 | 58 | 1.56 | 40 | 3/8 | 5/8 | 7/16 | 1.51 | 38 |
| 26920-5-5 | 5/16 | 1/2x20 | 1/4 | 2.55 | 65 | 1.65 | 42 | 7/16 | 11/16 | 1/2 | 1.72 | 44 |
| 26920-5-6 | 5/16 | 1/2x20 | 5/16 | 2.63 | 67 | 1.65 | 42 | 1/2 | 13/16 | 1/2 | 1.71 | 43 |
| 26920-6-6 | 3/8 | 5/8x18 | 5/16 | 2.67 | 68 | 1.69 | 43 | 1/2 | 13/16 | 5/8 | 1.75 | 44 |
| 26920-8-8 | 1/2 | 3/4x18 | 13/32 | 3.09 | 78 | 1.88 | 48 | 5/8 | 15/16 | 3/4 | 2.00 | 51 |



23220

Female PTT 30° - Swivel


| # Part Number | Thread | | Hose I.D. inch | A | | H | J | W | B | |
|------------------|--------|-----------|-------------------|------|----|-------|--------|-------|------|----|
| | inch | 1-5/16x14 | | inch | mm | inch | inch | inch | inch | mm |
| 23220-16-16 | 1 | 1-5/16x14 | 7/8 | 2.98 | 76 | 1-1/2 | 1-7/16 | 1-1/2 | 1.79 | 45 |



26120

Male SAE Compression Seat (without Nut or Sleeve)

| # Part Number | Thread | | Hose I.D. inch | A | | H | J | B | |
|------------------|--------|----------|-------------------|------|----|------|-------|------|----|
| | inch | 13/16x18 | | inch | mm | inch | inch | inch | mm |
| 26120-10-10 | 5/8 | 13/16x18 | 1/2 | 2.64 | 67 | 7/8 | 1-1/8 | 1.42 | 36 |



21520

SAE Code 61 Flange Head ISO 12151-3-S-L

| # Part Number | Flange inch | Hose I.D. inch | A | | F | H | J | B | |
|------------------|----------------|-------------------|------|-----|--------|-------|-------|------|----|
| | | | inch | mm | inch | inch | inch | inch | mm |
| 21520-20-20 | 1-1/4 | 1-1/8 | 3.58 | 91 | 2 | 1-1/2 | 1-3/4 | 2.30 | 58 |
| 21520-40-40 | 2-1/2 | 2-3/8 | 5.22 | 133 | 3-5/16 | 2-3/4 | 3-1/8 | 3.41 | 87 |

See Accesories Section for O-Rings and Flange Kits.

