2-Piece Domestic Stainless Steel Ball Valves

Features:

- pressure rating: 1,000 PSI Cold Working Pressure
- pressure rating: 150 PSI saturated steam
- · vacuum service to 29 inches Hg
- · 316 stainless body, ball and stem
- PTFE seal
- blow-out proof stem
- vinyl handle cover
- temperature range: -40°F to 400°F (-40°C to 204°C)

Female NPT	Port	316 Stainless Steel Part #
1/4"	full	DSBV25
3/8"	full	DSBV38
1/2"	full	DSBV50
3/4"	full	DSBV75
1"	full	DSBV100
11/4"	full	DSBV125
1½"	full	DSBV150
2"	full	DSBV200



Stainless Steel Ball Valves Full Port

Applications:

· for use with water, oil and gas

Features:

• pressure rating: $\frac{1}{4}$ " - 2" rated to **1000 PSI** WOG (CWP) $2\frac{1}{2}$ " - 3" rated to **800 PSI** WOG (CWP)

100 PSI saturated steam

- · 316 stainless steel body, ball and stem
- RPTFE seat, joint gasket and thrust washer
- blow-out proof stem design
- temperature range: -20°F to 446°F (-29°C to 230°C) as long as the valve is run fully open/ closed

Female NPT	Port	316 Stainless Steel Part #
1/4"	full	SSBV25
3/8"	full	SSBV38
1/2"	full	SSBV50
3/4"	full	SSBV75
1"	full	SSBV100
11/4"	full	SSBV125
1½"	full	SSBV150
2"	full	SSBV200
21/2"	full	SSBV250
3"	full	SSBV300

