

## Railroad Tank Car Connections

**Features:**

- all swivel nuts have standard 5" Railroad Tank Car thread
- supplied with a Buna-N gasket in the threaded end, other gaskets available on page 59
- also available in other materials and in 2" and 2½" sizes, consult Dixon® for pricing and availability

**Style A**

Stainless steel railroad tank car connections are not compatible with aluminum and brass.



Male Adapter	Swivel Nut	Elbow	316 Stainless Steel Part #	Aluminum Part #
3"	5"	120°	<b>RTCA30</b>	---
4"	5"	110°	<b>RTCA40<sup>1</sup></b>	<b>ATCA40</b>

<sup>1</sup> parts are produced as a welded fabrication

**Style F****Features:**

- 4" TTMA flange can be bolted to sight glass; API adapter or other dry disconnect
- supplied with PTFE Buna-N envelope gasket



110° elbow

TTMA Flange	Swivel Nut	Elbow	Aluminum Part #
4"	5"	110°	<b>ATCF40<sup>1</sup></b>
	5"	90°	<b>ATCF40-90</b>

<sup>1</sup> part is produced as a welded fabrication

- For flange dimensions, diagrams and additional information please reference [dixonvalve.com](http://dixonvalve.com).

**Style GF****Feature:**

- 4" TTMA flange can be bolted to sight glass; API adapter or other dry disconnect



110° elbow

TTMA Flange	Boss-lock™ Coupler	Elbow	Aluminum Part #
4"	4"	110°	<b>ATCGF40</b>
	4"	90°	<b>ATCGF40-90</b>

- For flange dimensions, diagrams and additional information please reference [dixonvalve.com](http://dixonvalve.com).

**Screen****Features:**

- stainless steel screen encapsulated in a buna gasket
- for use in Style GF elbows



Size	Hole Size	316L Stainless Steel Part #
4"	1"	<b>400-G-BUSS</b>

**Style S**

Shank Size	Swivel Nut	Elbow	Aluminum Part #
4"	5"	110°	<b>ATCS40</b>