

ADS Outage Gauge

**Applications:**

- set level fill point for manual / visual fill control
- measure outage requirements on mobile tanks

Feature:

- open dome bracket

Length	316 stainless steel Standard Outgauge Part #	316 stainless steel Outgauge with J Bar Part #
2'	A800OG2	A800OGJ2
3'	A800OG3	A800OGJ3
4'	A800OG4	A800OGJ4
5'	A800OG5	A800OGJ5

ADS Gauge Rods

**Application:**

- used to gauge liquid levels in any mobile tank

Features:

- ½" x .065 wt hardened 316 stainless steel
- laser engraved scale with ¼" graduations
- rods come in two sections that screw together at the midpoint
- foot marks inscribed on rod at 1' intervals below the inch mark
- heavy duty plastic handle
- available in 4', 8' and 12' lengths

Description	316 Stainless Steel Part #
4'	ADS4GR
8'	ADS8GR
12'	ADS12GR



laser engraving closeup

ADS Spillguard™ Armored Cables

Features:

- 3 or 5 pin connector
- 316 stainless steel armoured cable or yellow rubber cable
- custom lengths available, call 513.874.8499 or 877.582.3569 for more information

Armored Cables

Length	3 Pin	5 Pin
15'	A200CA3P15	A200CA5P15
20'	A200CA3P20	A200CA5P20
25'	A200CA3P25	A200CA5P25
50'	A200CA3P50	A200CA5P50

Rubber Cable ¹

Length	3 Pin
25'	A200CB3P25

¹ for use with (-M) mini connectors only