

## King Crimp™ Style Ferrules

Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon® products.



Hose ID	Hose OD		Work. Pressure (PSI)		Ferrule ID	Ferrule Wall Thickness	Ferrule Overall Length	Carbon Steel Part #	304 Stainless Steel Part #
	From	To	cam & groove <sup>1</sup>	King Crimp nipple <sup>2</sup>					
1"	1-13/64"	1-16/64"	*	*	1.313"	.062"	2-13/16"	<b>CF100-1CS</b>	<b>CF100-1SS</b>
	1-17/64"	1-20/64"	*	*	1.375"	.062"	2-13/16"	<b>CF100-2CS</b>	<b>CF100-2SS</b>
	1-21/64"	1-24/64"	*	*	1.438"	.062"	2-13/16"	<b>CF100-3CS</b>	<b>CF100-3SS</b>
	1-25/64"	1-28/64"	*	*	1.500"	.062"	2-13/16"	<b>CF100-4CS</b>	<b>CF100-4SS</b>
	1-29/64"	1-32/64"	*	*	1.563"	.062"	2-13/16"	<b>CF100-5CS</b>	<b>CF100-5SS</b>
	1-33/64"	1-36/64"	*	*	1.625"	.062"	2-13/16"	<b>CF100-6CS</b>	<b>CF100-6SS</b>
	1-37/64"	1-40/64"	*	*	1.688"	.062"	2-13/16"	<b>CF100-7CS</b>	<b>CF100-7SS</b>
	1-41/64"	1-44/64"	*	*	1.750"	.062"	2-13/16"	<b>CF100-8CS</b>	<b>CF100-8SS</b>
	1-45/64"	1-48/64"	*	*	1.813"	.062"	2-13/16"	<b>CF100-9CS</b>	<b>CF100-9SS</b>
	1-49/64"	1-52/64"	*	*	1.875"	.062"	2-13/16"	<b>CF100-10CS</b>	<b>CF100-10SS</b>
1 1/4"	1-41/64"	1-44/64"	250	350	1.750"	.060"	2-13/16"	<b>CF125-3CS</b>	<b>CF125-3SS</b>
	1-45/64"	1-48/64"	250	350	1.813"	.060"	2-13/16"	<b>CF125-4CS</b>	<b>CF125-4SS</b>
	1-49/64"	1-52/64"	250	350	1.875"	.060"	2-13/16"	<b>CF125-5CS</b>	<b>CF125-5SS</b>
	1-53/64"	1-56/64"	250	350	1.938"	.060"	2-13/16"	<b>CF125-6CS</b>	<b>CF125-6SS</b>
	1-41/64"	1-44/64"	250	350	1.750"	.062"	2-13/16"	<b>CF150-1CS</b>	<b>CF150-1SS</b>
1 1/2"	1-45/64"	1-48/64"	250	350	1.813"	.062"	2-13/16"	<b>CF150-2CS</b>	<b>CF150-2SS</b>
	1-49/64"	1-52/64"	250	350	1.875"	.062"	2-13/16"	<b>CF150-3CS</b>	<b>CF150-3SS</b>
	1-53/64"	1-56/64"	250	350	1.938"	.062"	2-13/16"	<b>CF150-4CS</b>	<b>CF150-4SS</b>
	1-57/64"	1-60/64"	250	350	2.000"	.062"	2-13/16"	<b>CF150-5CS</b>	<b>CF150-5SS</b>
	1-61/64"	2"	250	350	2.063"	.062"	2-13/16"	<b>CF150-6CS</b>	<b>CF150-6SS</b>
	2-1/64"	2-4/64"	250	350	2.125"	.062"	2-13/16"	<b>CF150-7CS</b>	<b>CF150-7SS</b>
	2-5/64"	2-8/64"	250	350	2.188"	.062"	2-13/16"	<b>CF150-8CS</b>	<b>CF150-8SS</b>
	2-9/64"	2-12/64"	250	350	2.250"	.062"	2-13/16"	<b>CF150-9CS</b>	<b>CF150-9SS</b>
	2-13/64"	2-16/64"	250	350	2.313"	.062"	2-13/16"	<b>CF150-10CS</b>	<b>CF150-10SS</b>
	2-17/64"	2-20/64"	250	350	2.375"	.062"	2-13/16"	<b>CF150-11CS</b>	<b>CF150-11SS</b>
	2-21/64"	2-24/64"	250	350	2.438"	.062"	2-13/16"	<b>CF150-12CS</b>	<b>CF150-12SS</b>
	2"	2-13/64"	2-16/64"	250	300	2.313"	.062"	3-1/8"	<b>CF200-1CS</b>
2-17/64"		2-20/64"	250	300	2.375"	.062"	3-1/8"	<b>CF200-2CS</b>	<b>CF200-2SS</b>
2-21/64"		2-24/64"	250	300	2.438"	.062"	3-1/8"	<b>CF200-3CS</b>	<b>CF200-3SS</b>
2-25/64"		2-28/64"	250	300	2.500"	.062"	3-1/8"	<b>CF200-4CS</b>	<b>CF200-4SS</b>
2-29/64"		2-32/64"	250	300	2.563"	.062"	3-1/8"	<b>CF200-5CS</b>	<b>CF200-5SS</b>
2-33/64"		2-36/64"	250	300	2.625"	.062"	3-1/8"	<b>CF200-6CS</b>	<b>CF200-6SS</b>
2-37/64"		2-40/64"	250	300	2.688"	.062"	3-1/8"	<b>CF200-7CS</b>	<b>CF200-7SS</b>
2-41/64"		2-44/64"	250	300	2.750"	.062"	3-1/8"	<b>CF200-8CS</b>	<b>CF200-8SS</b>
2-45/64"		2-48/64"	250	300	2.813"	.062"	3-1/8"	<b>CF200-9CS</b>	<b>CF200-9SS</b>
2-49/64"		2-52/64"	250	300	2.875"	.062"	3-1/8"	<b>CF200-10CS</b>	<b>CF200-10SS</b>
2-53/64"		2-56/64"	250	300	2.938"	.062"	3-1/8"	<b>CF200-11CS</b>	<b>CF200-11SS</b>
2-57/64"		2-60/64"	250	300	3.000"	.062"	3-1/8"	<b>CF200-12CS</b>	<b>CF200-12SS</b>

\* consult Dixon® at [engineering@dixonvalve.com](mailto:engineering@dixonvalve.com) for pressure rating

<sup>1</sup> based on using crimp cam & groove shanks

<sup>2</sup> based on using King™ crimp nipples

## King Crimp™ Style Ferrules



Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon® products.



Hose ID	Hose OD		Work. Pressure (PSI)		Ferrule ID	Ferrule Wall Thickness	Ferrule Overall Length	Carbon Steel Part #	304 Stainless Steel Part #
	From	To	cam & groove <sup>1</sup>	King Crimp nipple <sup>2</sup>					
3"	3-13/64"	3-16/64"	150	300	3.313"	.090"	4"	CF300-1CS	CF300-1SS
	3-17/64"	3-20/64"	150	300	3.375"	.090"	4"	CF300-2CS	CF300-2SS
	3-21/64"	3-24/64"	150	300	3.438"	.090"	4"	CF300-3CS	CF300-3SS
	3-25/64"	3-28/64"	150	300	3.500"	.090"	4"	CF300-4CS	CF300-4SS
	3-29/64"	3-32/64"	150	300	3.563"	.090"	4"	CF300-5CS	CF300-5SS
	3-33/64"	3-36/64"	150	300	3.625"	.090"	4"	CF300-6CS	CF300-6SS
	3-37/64"	3-40/64"	150	300	3.688"	.090"	4"	CF300-7CS	CF300-7SS
	3-41/64"	3-44/64"	150	300	3.750"	.090"	4"	CF300-8CS	CF300-8SS
	3-45/64"	3-48/64"	150	300	3.813"	.090"	4"	CF300-9CS	CF300-9SS
	3-49/64"	3-52/64"	150	300	3.875"	.090"	4"	CF300-10CS	CF300-10SS
	3-53/64"	3-56/64"	150	300	3.938"	.090"	4"	CF300-11CS	CF300-11SS
	3-57/64"	3-60/64"	150	300	4.000"	.090"	4"	CF300-12CS	CF300-12SS
	3-61/64"	4"	150	300	4.063"	.090"	4"	CF300-13CS	CF300-13SS
	4-1/64"	4-4/64"	150	300	4.125"	.090"	4"	CF300-14CS	CF300-14SS
	4-5/64"	4-8/64"	150	300	4.188"	.090"	4"	CF300-15CS	CF300-15SS
	4-9/64"	4-12/64"	150	300	4.250"	.090"	4"	CF300-16CS	CF300-16SS
4"	4-13/64"	4-16/64"	150	300	4.313"	.090"	4"	CF400-1CS	CF400-1SS
	4-17/64"	4-20/64"	150	300	4.375"	.090"	4"	CF400-2CS	CF400-2SS
	4-21/64"	4-24/64"	150	300	4.438"	.090"	4"	CF400-3CS	CF400-3SS
	4-25/64"	4-28/64"	150	300	4.500"	.090"	4"	CF400-4CS	CF400-4SS
	4-29/64"	4-32/64"	150	300	4.563"	.090"	4"	CF400-5CS	CF400-5SS
	4-33/64"	4-36/64"	150	300	4.625"	.090"	4"	CF400-6CS	CF400-6SS
	4-37/64"	4-40/64"	150	300	4.688"	.090"	4"	CF400-7CS	CF400-7SS
	4-41/64"	4-44/64"	150	300	4.750"	.090"	4"	CF400-8CS	CF400-8SS
	4-45/64"	4-48/64"	150	300	4.813"	.090"	4"	CF400-9CS	CF400-9SS
	4-49/64"	4-52/64"	150	300	4.875"	.090"	4"	CF400-10CS	CF400-10SS
	4-53/64"	4-56/64"	150	300	4.938"	.090"	4"	CF400-11CS	CF400-11SS
	4-57/64"	4-60/64"	150	300	5.000"	.090"	4"	CF400-12CS	CF400-12SS
	4-61/64"	5"	150	300	5.063"	.090"	4"	CF400-13CS	CF400-13SS
	5-1/64"	5-4/64"	150	300	5.125"	.090"	4"	CF400-14CS	CF400-14SS
	5-5/64"	5-8/64"	150	300	5.188"	.090"	4"	CF400-15CS	CF400-15SS
	5-9/64"	5-12/64"	150	300	5.250"	.090"	4"	CF400-16CS	CF400-16SS
6"	6-21/64"	6-28/64"	*	*	6.500"	.120"	5-7/8"	CF600-1CS	CF600-1SS
	6-29/64"	6-36/64"	*	*	6.625"	.120"	5-7/8"	CF600-2CS	CF600-2SS
	6-37/64"	6-44/64"	*	*	6.750"	.120"	5-7/8"	CF600-3CS	CF600-3SS
	6-45/64"	6-52/64"	*	*	6.875"	.120"	5-7/8"	CF600-4CS	CF600-4SS
	6-53/64"	6-60/64"	*	*	7.000"	.120"	5-7/8"	CF600-5CS	CF600-5SS
	6-61/64"	7-4/64"	*	*	7.125"	.120"	5-7/8"	CF600-6CS	CF600-6SS
	7-5/64"	7-12/64"	*	*	7.250"	.120"	5-7/8"	CF600-7CS	CF600-7SS
	7-13/64"	7-20/64"	*	*	7.375"	.120"	5-7/8"	CF600-8CS	CF600-8SS
	7-21/64"	7-28/64"	*	*	7.500"	.120"	5-7/8"	CF600-9CS	CF600-9SS

\* consult Dixon® at [engineering@dixonvalve.com](mailto:engineering@dixonvalve.com) for pressure rating

<sup>1</sup> based on using crimp cam & groove shanks

<sup>2</sup> based on using King™ crimp nipples