

F16 Compact Airline Filters


Features:

- 5 micron element
- 2.7 oz. bowl
- maximum operating conditions:
 - transparent bowl: **150 PSIG** (10.3 bar) and **32°F to 125°F (0°C to 52°C)**
 - metal bowl: **200 PSIG** (13.8 bar) and **32°F to 150°F (0°C to 65.5°C)**

Size	Flow (SCFM)	Transparent Bowl and Guard		Metal Bowl	
		Automatic Drain Part #	Manual Drain Part #	Automatic Drain Part #	Manual Drain Part #
¼"	63.0	F16-02A	F16-02M	F16-02AMB	F16-02MMB
⅜"	74.1	F16-03A	F16-03M	F16-03AMB	F16-03MMB
½"	80.4	F16-04A	F16-04M	F16-04AMB	F16-04MMB



with guard



Pneumatic Accessories

F18 Compact Airline Filters


Features:

- high flow capacity
- 5 micron element
- 1.72 oz. bowl
- maximum operating conditions:
 - transparent bowl: **150 PSIG** (10.3 bar) and **32°F to 125°F (0°C to 52°C)**
 - metal bowl: **250 PSIG** (17.2 bar) and **32°F to 150°F (0°C to 65.5°C)**

Size	Flow (SCFM)	Transparent Bowl and Guard		Metal Bowl with Sight Glass	
		Automatic Drain Part #	Manual Drain Part #	Automatic Drain Part #	Manual Drain Part #
¼"	110	F18-02A	F18-02M	F18-02AMB	F18-02MMB
⅜"	120	F18-03A	F18-03M	F18-03AMB	F18-03MMB
½"	145	F18-04A	F18-04M	F18-04AMB	F18-04MMB



transparent bowl with guard



F26 Standard Airline Filters


Features:

- 5 micron element
- 3.2 oz. bowl
- maximum operating conditions:
 - transparent bowl: **150 PSIG** (10.3 bar) and **32°F to 125°F (0°C to 52°C)**
 - metal bowl: **200 PSIG** (13.8 bar) and **32°F to 150°F (0°C to 65.5°C)**

Size	Flow (SCFM)	Transparent Bowl and Guard		Metal Bowl with Sight Glass	
		Automatic Drain Part #	Manual Drain Part #	Automatic Drain Part #	Manual Drain Part #
¼"	81.3	F26-02A	F26-02M	F26-02AMB	F26-02MMB
⅜"	117.8	F26-03A	F26-03M	F26-03AMB	F26-03MMB
½"	149.8	F26-04A	F26-04M	F26-04AMB	F26-04MMB



with guard



See pages 401 to 405 for accessories.

! FRL's are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure.