

Premium Duty Spring Retractable Hose Reels

Air/Water/Oil/Grease - 1/4", 3/8", 1/2", 3/4" I.D.

- Retracts at the average human walking speed of 2 to 3 MPH
- Integral clutch creates a consistent retraction speed regardless of fluid or environmental temperatures
- Safely protects personnel and equipment

NEW!
Controlled
Return Hose Reel
REELSAFE



RS7650 OLP



Additional Series RS7000 Models

Gas Welding Reels - Page 33

| Model with hose & bumper | Shipping Weight | | Hose I.D. | | Hose O.D. | | Hose Length | | Max Pressure | | NPT(M) Hose Outlet | NPT(F) Reel Inlet | NPT(F) Reel Outlet |
|---|-----------------|----|-----------|----|-----------|----|-------------|----|--------------|-----|--------------------|-------------------|--------------------|
| | lbs | kg | in | mm | in | mm | ft | m | psi | bar | in | in | in |
| Low Pressure Air/Water Reels Maximum Temperature 150 °F (65 °C) Max working pressure is at 70 °F (20 °C) | | | | | | | | | | | | | |
| RS7650 OLP | 46 | 21 | 3/8 | 10 | .600 | 15 | 50 | 15 | 300 | 21 | 1/4 | 1/2 | 1/2 |
| RS7670 OLP ★ | 50 | 23 | 3/8 | 10 | .600 | 15 | 70 | 22 | 300 | 21 | 1/4 | 1/2 | 1/2 |
| RS7850 OLP ★ | 50 | 23 | 1/2 | 13 | .750 | 19 | 50 | 15 | 300 | 21 | 3/8 | 1/2 | 1/2 |
| RS7925 OLP | 50 | 23 | 3/4 | 19 | 1.075 | 27 | 25 | 8 | 250 | 17 | 3/4 | 3/4 | 3/4 |
| Medium Pressure Oil Reels Maximum Temperature 210 °F (99 °C) | | | | | | | | | | | | | |
| RS7650 OMP | 58 | 26 | 3/8 | 10 | .690 | 18 | 50 | 15 | 2600 | 179 | 3/8 | 1/2 | 1/2 |
| RS7850 OMP ★ | 60 | 27 | 1/2 | 13 | .820 | 21 | 50 | 15 | 3000 | 207 | 1/2 | 1/2 | 1/2 |
| High Pressure Grease Reels Maximum Temperature 210 °F (99 °C) | | | | | | | | | | | | | |
| RS7450 OHP | 58 | 26 | 1/4 | 6 | .580 | 15 | 50 | 15 | 5000 | 345 | 1/4 | 1/2 | 1/2 |
| RS7650 OHP | 63 | 29 | 3/8 | 10 | .730 | 19 | 50 | 15 | 4800 | 331 | 1/4 | 1/2 | 1/2 |

Low pressure reels supplied with PVC hose. Medium pressure reels supplied with S.A.E. 100R1-AT (3/8") or S.A.E. 100R17 (1/2") one wire braid hose. High pressure reels supplied with S.A.E. 100 R2T two wire braid hose.

| Dimensions | | | | | |
|------------|--------------------------------|--------------------------------|---------------------------------|-------------------------------|-----|
| | A | B | C | D | E |
| in | 20 ¹ / ₄ | 19 ³ / ₄ | 7 ¹³ / ₁₆ | 3 ⁷ / ₈ | 7 |
| mm | 514 | 502 | 198 | 98 | 178 |

| Model without hose & bumper | Shipping Weight | | Hose Capacity | | | Max Pressure | NPT(F) Reel Inlet | NPT(F) Reel Outlet | | |
|--|-----------------|----|---------------|------|--------|--------------|-------------------|--------------------|-----|-----|
| | lbs | kg | I.D. | O.D. | Length | | | | | |
| Low Pressure Air/Water Reels Maximum Temperature 210 °F (99 °C) | | | | | | | | | | |
| RS7600 OLP | 43 | 20 | 3/8 | 10 | .600 | 16 | 500 | 35 | 1/2 | 1/2 |
| RS7800 OLP | 44 | 20 | 1/2 | 13 | .750 | 19 | 500 | 35 | 1/2 | 1/2 |
| Medium Pressure Oil Reels Maximum Temperature 210 °F (99 °C) | | | | | | | | | | |
| RS7600 OMP | 46 | 21 | 3/8 | 10 | .690 | 18 | 3000 | 207 | 1/2 | 1/2 |
| High Pressure Grease Reels Maximum Temperature 210 °F (99 °C) | | | | | | | | | | |
| RS7400 OHP | 46 | 21 | 1/4 | 6 | .580 | 15 | 5000 | 345 | 1/2 | 1/2 |
| RS7600 OHP | 49 | 27 | 3/8 | 10 | .730 | 19 | 5000 | 345 | 1/2 | 1/2 |



Pivot Bases & Swing Brackets
See page 39

Premium Duty Enclosed Hose Reels

Air/Water - 1/4", 3/8", 1/2" I.D.

- Features a steel enclosure that offers an additional level of protection for the hose
- Remove the cover on either side for easy access

5450 ELP



| | 1 | | 2 | |
|----------|--------------------------------|-----|---------------------------------|-----|
| | in | mm | in | mm |
| A | 15 | 381 | 20 ⁷ / ₈ | 530 |
| B | 16 ¹ / ₄ | 413 | 21 ¹ / ₈ | 537 |
| C | 9 ³ / ₄ | 248 | 7 ¹³ / ₁₆ | 198 |
| D | 2 ¹ / ₂ | 64 | 3 ⁷ / ₈ | 98 |
| E | 7 | 178 | 7 ⁵ / ₈ | 194 |

| Model with hose & bumper | Shipping Weight | | Hose I.D. | Hose O.D. | Hose Length | | Max Pressure | NPT(M) Hose Outlet | NPT(F) Reel Inlet | NPT(F) Reel Outlet | Size Index # | |
|--|-----------------|----|-----------|-----------|-------------|----|--------------|--------------------|-------------------|--------------------|--------------|---|
| | lbs | kg | | | ft | m | | | | | | |
| Low Pressure Air/Water Reels Maximum Temperature 150 °F (65 °C) Max working pressure is 70 °F (20 °C) | | | | | | | | | | | | |
| 5450 ELP | 37 | 17 | 1/4 | 6 | .475 | 12 | 300 | 21 | 1/4 | 3/8 | 1/4 | 1 |
| 7650 ELP | 63 | 29 | 3/8 | 10 | .600 | 15 | 300 | 21 | 1/4 | 1/2 | 1/2 | 2 |
| 7670 ELP | 68 | 31 | 3/8 | 10 | .600 | 15 | 300 | 21 | 1/4 | 1/2 | 1/2 | 2 |
| 7850 ELP | 74 | 34 | 1/2 | 13 | .750 | 19 | 300 | 21 | 3/8 | 1/2 | 1/2 | 2 |