



## T-Bolt Clamps

## Features:

## Style TBC

- can be applied with a standard 7/16" socket wrench
- 3/4" wide, .025" thick, 300 series stainless steel band
- alloy steel bolt, torque rating: 70 in/lbs
- not for use with pneumatic tools 

## Style STBC

- can be applied with a standard 7/16" socket wrench
- 3/4" wide, .025" thick, 300 series stainless steel band
- 300 series stainless steel bolt, torque rating: 50 in/lbs
- not for use with pneumatic tools 

Clamps



style TBC



style STBC

Hose OD		style TBC Part #	Hose OD		style STBC Part #	Optional Qty
from	to		from	to		
1.25"	1.406"	<b>TBC131</b>	1.25"	1.4063"	<b>STBC131</b>	25
1.34"	1.56"	<b>TBC150</b>	1.31"	1.56"	<b>STBC150</b>	25
1.56"	1.81"	<b>TBC175</b>	1.44"	1.69"	<b>STBC163</b>	25
1.69"	1.94"	<b>TBC188</b>	1.56"	1.81"	<b>STBC175</b>	25
1.81"	2.06"	<b>TBC200</b>	1.69"	1.94"	<b>STBC188</b>	25
2.06"	2.31"	<b>TBC225</b>	1.81"	2.06"	<b>STBC200</b>	25
2.19"	2.5"	<b>TBC238</b>	1.93"	2.18"	<b>STBC212</b>	25
2.31"	2.62"	<b>TBC250</b>	2.06"	2.31"	<b>STBC225</b>	25
2.31"	2.62"	<b>TBC256</b>	2.19"	2.5"	<b>STBC238</b>	25
2.37"	2.68"	<b>TBC263</b>	2.31"	2.62"	<b>STBC250</b>	25
2.50"	2.81"	<b>TBC275</b>	2.31"	2.62"	<b>STBC256</b>	25
2.63"	2.94"	<b>TBC288</b>	2.37"	2.68"	<b>STBC263</b>	25
2.75"	3.06"	<b>TBC300</b>	2.50"	2.81"	<b>STBC275</b>	25
2.88"	3.19"	<b>TBC312</b>	2.63"	2.94"	<b>STBC288</b>	25
3.00"	3.31"	<b>TBC325</b>	2.75"	3.06"	<b>STBC300</b>	25
3.25"	3.56"	<b>TBC350</b>	2.88"	3.19"	<b>STBC312</b>	25
3.50"	3.81"	<b>TBC375</b>	3.00"	3.31"	<b>STBC325</b>	25
3.56"	3.87"	<b>TBC382</b>	3.25"	3.56"	<b>STBC350</b>	25
3.75"	4.06"	<b>TBC400</b>	3.38"	3.69"	<b>STBC362</b>	25
4.00"	4.30"	<b>TBC425</b>	3.50"	3.81"	<b>STBC375</b>	25
4.25"	4.56"	<b>TBC450</b>	3.56"	3.87"	<b>STBC382</b>	25
4.50"	4.81"	<b>TBC475</b>	3.75"	4.06"	<b>STBC400</b>	25
4.75"	5.06"	<b>TBC500</b>	4.00"	4.30"	<b>STBC425</b>	25
5.00"	5.31"	<b>TBC525</b>	4.25"	4.56"	<b>STBC450</b>	25
5.25"	5.56"	<b>TBC550</b>	4.50"	4.81"	<b>STBC475</b>	25
5.50"	5.81"	<b>TBC575</b>	4.75"	5.06"	<b>STBC500</b>	25
5.75"	6.06"	<b>TBC600</b>	5.00"	5.31"	<b>STBC525</b>	25
6.00"	6.31"	<b>TBC625</b>	5.25"	5.56"	<b>STBC550</b>	25
6.25"	6.56"	<b>TBC650</b>	5.50"	5.81"	<b>STBC575</b>	25
6.50"	6.81"	<b>TBC675</b>	5.75"	6.06"	<b>STBC600</b>	25
6.75"	7.06"	<b>TBC700</b>	6.00"	6.31"	<b>STBC625</b>	25
7.25"	7.56"	<b>TBC750</b>	6.25"	6.56"	<b>STBC650</b>	25
			6.50"	6.81"	<b>STBC675</b>	25
			6.75"	7.06"	<b>STBC700</b>	25
			7.00"	7.31"	<b>STBC725</b>	25
			7.25"	7.56"	<b>STBC750</b>	25
			7.75"	8.06"	<b>STBC800</b>	25
			8.00"	8.31"	<b>STBC825</b>	25
			8.25"	8.56"	<b>STBC850</b>	25
			8.63"	8.94"	<b>STBC888</b>	25
			8.75"	9.06"	<b>STBC900</b>	25
			9.25"	9.56"	<b>STBC950</b>	25
			9.75"	10.06"	<b>STBC1000</b>	10
			10.63"	10.94"	<b>STBC1088</b>	10
			11.75"	12.06"	<b>STBC1200</b>	10
			12.63"	12.94"	<b>STBC1288</b>	10