


## Flat Hex Manifolds

**Feature:**

- designed to lay flat on the floor, safely distributing three hose lines to the work area

NPT Inlet (1)	NPT Outlets (3)	Brass Part #
1/4"	1/4"	<b>3122</b>
3/8"	1/4"	<b>3132</b>
3/8"	3/8"	<b>3133</b>



## Compressor Y

**Feature:**

- converts a single supply source to a dual outlet

Female NPT Inlet (1)	Male NPT Outlets (2)	Iron Part #
1"	3/4"	<b>Y10075</b>



## Anti-Freeze Lubricants

**Application:**

- winter grade air tool lubricant prevents air line, air tool and in-line lubricator freeze-up

**Features:**

- can be poured directly into tool or used with air line lubricators
- minimum temperature **-45°F (-43°C)**

Size	Part #	Optional Qty
1 pint	<b>DATL016W</b>	12
1 gallon	<b>DATL128W</b>	4



pint



gallon

## Air Tool Lubricants

**Application:**

- high grade lubricant prolongs the service life of air tools, cylinders and accessories

**Features:**

- #10 weight lubricant
- compound is superior in performance to ordinary lubricants
- prohibits rust and removes moisture as it lubricates
- non-corrosive, non-reactive and does not decompose
- easy pour spout helps prevent costly spills
- use with the in-line lubricators on page 368

Size	Part #	Optional Qty
1 pint	<b>DATL016</b>	12
1 gallon	<b>DATL128</b>	4



pint



gallon